

PRODUCT SPECIFICATIONS

Blyott Sticker Sensor With Battery BT-BS

Start monitoring and locating your assets now

Our Blyott Standard Sensor (BT-T1) has been widely deployed for many different types of applications. But in some use cases, the Blyott sensor size is less suited. So, what's the alternative?

Say hello to the BT-BS, also referred to as the world's thinnest battery-powered BLE sticker sensor.

BT-BS is a battery-powered sensor to track some of your smaller mobile assets, for instance, laptops and tablets.

Due to its multiple sensing capabilities, excellent data ranges, and extremely thin format, the BT-BS is really in a class of its own.

The built-in location and temperature sensors further enhance the overall functionalities. Use cases are many, including cold chain monitoring of medicines, localization of consumables, and electronic devices like laptops and tablets.

In combination with the Blyott Mobile Locator (BT-M1), you can easily upgrade standard cabinets to smart cabinets, monitor where medicines are stored, track times of pick up, and view the live inventory. Finally, the BT-BS is also an excellent solution for consignment challenges in healthcare environments.



The BT-BS is a revolutionary new battery-powered BLE sticker sensor.

Plug-and-play asset tracking

- 1 Download the Blyott mobile app.
- 2 Attach BT-BS on an asset.
- 3 Scan the barcode of the asset.
- 4 Scan the QR code of the sensor.
- 5 Press "link" and your asset is now being tracked.

TURN THE PAGE TO VIEW ALL SPECIFICATIONS. →

All specifications BT-BS

General

Battery reference	Printed zinc and manganese dioxide battery
Battery lifetime	Up to 5 years based upon BLE advertising intervals
Broadcasting range	Up to 15 m / 590.55" (-5 dBm; RSSI @ 12 m / 472.44" = -100 dBm)
Connectivity	BLE 4.0 and above
Security	AES-128, encryption and authentication

Physical

Dimensions	60 mm / 2.36" (width) x 60 mm / 2.36" (length) x < 1 mm / < 0.03" (height)
Colors	White
Material	Clear PET with adhesive

Chemical and mechanical

Operating temperature	0°C to +60°C / +32°F to +140°F
Environmental and chemical properties	IP65, saltwater, salt mist, acetic acid water, carbonated sodium water, sugared water, ethylene glycol, humidity 95% (50°C / 122°F, 24h)
Certificates	FCC, IC, Japan Radio Law and CE mark in the future

About Blyott

Blyott is at the forefront of transforming industries with innovative localization and monitoring solutions. Our platform integrates advanced data analytics and AI, supporting various sectors to navigate operational challenges, enhance efficiency, foster staff well-being, and achieve sustainability goals.



EASY TO SET UP

Works in a matter of minutes.



SCALABLE

Scale to millions of assets.



PAY-AS-YOU-GROW

Custom plans are available.



OPEN STANDARD

Integrate using REST APIs and webhooks.



www.blyott.com

Kappellestraat 138/0-02
8020 Oostkamp
Belgium

Get in touch at
info@blyott.com