

## PRODUCT SPECIFICATIONS

# Blyott Heat Sensor BT-R2

## Start monitoring and locating your assets now

Meet the BT-R2, a BLE sensor capable of surviving high temperatures. The BLE V5.3 compliant module comes with a secure, custom firmware and a waterproof, easy-to-clean casing.

BT-R2 helps you keep track of your (mobile) assets and is well-suited for extreme conditions.

**Support temperatures up to 150°C, making the BT-R2 ideal for tracking instrument trays and other assets undergoing sterilization processes.**

The BT-R2 casing is crafted from silicone, a material known for its biocompatibility, durability, and resistance to extreme temperatures.

These qualities make it well-suited for healthcare applications, where long-lasting performance, safety, and stability are essential. Its built-in loop also enables easy attachment to assets, such as surgical kits.

With optimized and ultra-low power consumption, the sensor guarantees a very long battery life, even when exposed to extreme conditions.

Finally, a secure operational mode is included and based on an AES-128 crypto algorithm.



*The built-in NFC makes it extremely easy to link the BT-R2 to assets.*

### Highlighted use case

- ✓ Track medical equipment and surgical trays during the sterilization processes.
- ✓ A built-in loop allows for easy usage, e.g. attach the BT-R2 to instrument trays.
- ✓ Start using immediately with no sensor activation required.

TURN THE PAGE TO VIEW ALL SPECIFICATIONS. →

# All specifications BT-R2

## General

Battery reference	CR2032W (heat-resistant lithium ion battery)
Battery lifetime	Up to 5 years depending on the sensor configuration and usage
Broadcasting range	Up to 15 m / 590.55" (-5 dBm; RSSI @ 12 m / 472.44" = -100 dBm)
Location accuracy	Depends on the available Wi-Fi and Bluetooth <sup>®</sup> infrastructure
Temperature accuracy	Temperature sensor with an accuracy of 2°C / 35.6°F
Connectivity	Built in NFC

<sup>®</sup>The Blyott solution is compatible with Wi-Fi AP's enabled with Bluetooth<sup>®</sup> technology from various vendors. Bluetooth<sup>®</sup> is a registered trademark of Bluetooth SIG, Inc.

## Physical

Dimensions	40 mm / 1.57" (diameter) x 7 mm / 0.27" (height) x 80 mm / 3.14" (length of loop)
Colours	Dark blue
Casing	Silicone, highly durable casing for temperatures up to 200°C

## Chemical and mechanical

Operating temperature	-20°C to +150°C / -4°F to +302°F (during a few minutes)
Humidity	100% (up to 150 °C / +302°F)
Environmental and chemical properties	Saltwater, salt mist, acetic acid water, carbonated sodium water, sugared water, ethylene glycol
Certificates	IP68, CE-RED (incl. safety, RF, EMC, SAR), FCC and ROHS

## About Blyott

Blyott is at the forefront of transforming industries with innovative localization and monitoring solutions. Our platform integrates advanced data analytics and AI, supporting various sectors to navigate operational challenges, enhance efficiency, foster staff well-being, and achieve sustainability goals.



### EASY TO SET UP

Works in a matter of minutes.



### SCALABLE

Scale to millions of assets.



### PAY-AS-YOU-GROW

Custom plans are available.



### OPEN STANDARD

Integrate using REST APIs and webhooks.



[www.blyott.com](https://www.blyott.com)

Kappellestraat 138/0-02  
8020 Oostkamp  
Belgium

Get in touch at  
[info@blyott.com](mailto:info@blyott.com)